



FIBRE ROPES



The all purpose 8-strand plaited, high performance mooring rope. Features an extreme high breaking load and low weight, whilst still floating. Produced under the latest EN and ISO standards.



SPECIFIC GRAVITY	• 0,92	CONSTRUCTION	• 8-strand plaited
UV-RESISTANCE	• good	TCLL VALUE	• 52%
ABRASION RESISTANCE	• good	COLOUR	• white
CHEMICAL RESISTANCE	• good	MARKER YARN	• orange
ELONGATION	• see graph	WATERABSORPTION	• 0,1%
MELTING POINT	• approx. 165°C		

Art.number	Circ. (inches)	Diameter (mm)	Weight (kg/100m)	MBF (kN)
120.270	4	32	50,3	200
120.275	4 1/2	36	63,8	250
120.290	5	40	79,0	305
120.295	5 1/2	44	95,0	364
120.310	6	48	113	428
120.311	6 1/2	52	133	496
120.312	7	56	154	570
120.313	7 1/2	60	177	648
120.314	8	64	201	732
120.316	8 1/2	68	227	823
120.317	9	72	255	915
120.318	9 1/2	76	284	1020
120.319	10	80	314	1120
120.320	11	88	380	1340
120.321	12	96	453	1580

Diameter, weight and MBF (as well as other mechanical and physical properties) are determined according ISO 2307:2005

