



A dedicated floating winchline, developed especially to be used on single drum, self-tensioning winches. The load-bearing 7-strand core combines high strength and low elongation. The non load-bearing braided cover provides protection to the core (longer life-time) and increases crew-safety by minimizing the risk of snap-back. The smooth operation of the vessel is increased by the ease of handling of the rope due to its low weight and the floating characteristic of the rope.

Tipto Winchline® does not lose strength when wet!



# TIPTO WINCHLINE®



SPECIFIC GRAVITY	• 0,93	CONSTRUCTION	• 7-strand + jacket
UV-RESISTANCE	• very good	COLOUR	• yellow
ABRASION RESISTANCE	• very good	MARKER YARN	• orange
CHEMICAL RESISTANCE	• good	WATERABSORPTION	• 0%
ELONGATION	• see graph	ON REQUEST	• larger diameters
MELTING POINT	• approx. 135°C		

Art.number	Diameter (mm)	Weight (kg/100m)	MBF (kN)
111.952	36	74,0	248
111.953	42	98,0	340
111.934	46	115	425
111.956	48	125	472
111.935	50	133	512
111.936	54	150	598
111.896	56	160	640
111.937	58	167	682
111.967	60	184	730
111.966	62	190	780
111.938	64	203	850
111.939	68	221	934
111.970	70	240	990
111.940	74	256	1100
111.941	80	330	1270
111.942	82	356	1350
111.898	84	376	1420

### Larger diameters on request

Diameter, weight and MBF (as well as other mechanical and physical properties) are determined according ISO 2307:2005

