



FIBRE ROPES

A floating high performance rope constructed from high strength polypropylene and polyester yarns. Produced under the latest EN and ISO standards.



EUROFLOAT®



SPECIFIC GRAVITY	• 0,99 (floating)
UV-RESISTANCE	• good
ABRASION RESISTANCE	• very good
CHEMICAL RESISTANCE	• good
ELONGATION	• see graph
MELTING POINT	• approx. 165°C/265°C
CONSTRUCTION	• 8-strand plaited
TCLL VALUE	• 73 %
COLOUR	• white
MARKER YARN	• one yellow and one blue in one strand
WATERABSORPTION	• 0,1%

Art.number	Circ. (inches)	Diameter (mm)	Weight (kg/100m)	MBF (kN)
152.332	4	32	50,3	200
152.336	4 1/2	36	63,8	250
152.340	5	40	79,0	305
152.344	5 1/2	44	95,0	364
152.348	6	48	113	428
152.352	6 1/2	52	133	496
152.356	7	56	154	570
152.360	7 1/2	60	177	648
152.364	8	64	201	732
152.368	8 1/2	68	227	823
152.372	9	72	255	915
152.376	9 1/2	76	284	1020
152.380	10	80	314	1120
152.388	11	88	380	1340
152.396	12	96	453	1580

Diameter, weight and MBF (as well as other mechanical and physical properties) are determined according ISO 2307:2005

